

INSTALLATION
INSTRUCTIONS

FIXTURE TYPE _____

P-ID-82MS00
LK OPTION

P/C 510566-0000

PG. 1 OF 2

DO NOT MODIFY OR ALTER THIS PRODUCT IN ANY WAY, OR INSTALL IN ANY FASHION WHICH IS CONTRARY TO THE INSTRUCTIONS CONTAINED HEREIN.
IF YOU HAVE ANY QUESTIONS REGARDING THIS PRODUCT OR THE INSTALLATION OF IT, PLEASE CALL LITECONTROL ENGINEERING AT 781-294-0100.

GENERAL NOTES:

LENSES ARE SHIPPED SEPARATELY.
LENSES ARE INSTALLED AFTER FIXTURES HAVE BEEN MOUNTED AND WIRING HAS BEEN COMPLETED. REFER TO FIXTURE INSTRUCTION SHEET 510557.
LENS SURFACES CAN BE CLEANED WITH A DAMP CLOTH.
LENS ANGLES HAVE BEEN FACTORY INSTALLED BUT CAN ALSO BE ATTACHED IN THE FIELD AFTER FIXTURES HAVE BEEN SHIPPED. THIS CAN BE DONE BY LOOSENING THE INDIRECT REFLECTOR MOUNTING SCREWS AND SLIDING ANGLES OVER SCREWS UNTIL THEY SEAT ON TOP SURFACE OF FIXTURE. REFER TO DETAIL "A" ON PAGE 2.

INSTRUCTIONS:

1. FIXTURES ARE SHIPPED WITH BRIDGE TAPED IN PLACE, REMOVE TAPE AND LIFT OFF BRIDGE. INSTALL LAMPS AND REPLACE BRIDGE OVER LAMPS.
2. PEEL OFF PROTECTIVE PAPER COATING ON LENSES AND LAY LENS ONTO LENS ANGLES.
3. CENTER LENS ALONG LENGTH OF FIXTURE OPENING AND BEND TABS ON LENS ANGLES DOWNWARD TO SECURE LENS IN PLACE.



