




Type:
Project:

Mantra jr™
P-ID-37JR
Suspended Indirect/Direct

Specifications



HOUSING. Bottom housing is 23" in diameter, 16-gauge spun steel. Recessed chassis is 20-gauge spun steel.


REFLECTOR. Die-formed specular hammertone aluminum.

INDIRECT/DIRECT VERSION. P-ID-37JR incorporates a 2D direct lamp in the center of the fixture and a 16 7/8" diameter 1/8" thick white acrylic bowl (WAB) as downlight shield.

LAMPING. The upright component can accommodate four 26-, 32-, or 42-watt triple-tube compact fluorescent lamps. The optional downlight component can accommodate one 21-watt 2D lamp.

BALLAST. Electronic Ballast (ELB), high power factor, thermally protected Class P, Sound Rated A, manufactured by a UL Listed manufacturer, as available, determined by Litecontrol. The minimum number of ballasts will be used.

SUSPENSION. Each fixture is suspended with one P6S stem (5/8" dia., 3/8" NPT), or one P6S stem plus three aircraft cables and an intermediate retaining plate. The minimum recommended total suspension length is 18".

CERTIFICATION. Fixture and electrical components shall be UL Listed and shall bear the I.B.E.W., A.F. of L. label. 

Note: Litecontrol reserves the right to change specifications without notice for product development and improvement.

Ordering guide

Product, lamping, & length							Options				
P -	ID -	37JR	4	0	T26 /	21-2D -	WAB -	TCWM -	ELB -	F -	120
Mounting	Distribution	Series	Lamp Count	Nominal Length(ft)	Indirect Lamp Type	Direct Lamp Type	Diffuser	Finish	Ballast	Other options	Volts
P Pendant-Mounted	ID Indirect/ Direct	37JR	4 →	0	T26 T32 T42	21-2D	WAB	TCWM (Textured Matte White) is standard see LiteColors™ in Product Guide for other finishes	ELB is standard LPD/ELB see Ballast options	F see Other options	120 277
Mounting Options - add to end of order number <input type="checkbox"/> P6S/ACC standard <input type="checkbox"/> P6S							notes: For Ordering guide information in shaded areas, choose selection by reading ACROSS the shaded areas for correct specifications.				

Cross-sections



P-ID-37JR40T26/21-2D-WAB-TCWM-ELB-F-120-P6S/ACC18" is a typical catalog number for a 4-lamp indirect 26-watt triple-tube compact fluorescent and 1-lamp direct 21-watt 2D compact fluorescent fixture with white acrylic bowl diffuser, Textured Matte White finish, electronic ballast, fuse, 120 volts, and combination stem/cable mounting with 18" suspension.

Questions to Ask

1. 120 or 277 volt? 2. White, LiteColor, or special color?
3. Dimension "X": advise length and type of suspension required. 4. Other options?